

Pedestrian Entrance Control

Face Recognition - EvolveFace 5T





EvolveFace 5T

EvolveFace 5T detection face recognition terminal with time, attendance and temperature sensor.

Before allowing entry the forehead temperature sensor will check the persons temperature and decides whether to allow entry or not.



FEATUERS

- Size h154 x w152 x d22mm.
- Linux OS System.
- Detection time less than 0.2s.
- Adjustable read distance from 0.5 to 3m.
- Live face detection.
- LED and Infrared light for night use.
- Live movement detection.
- Duplicate face read, timeout period 1 to 20 seconds.
- 3,000 face capacity.
- Outputs = Wiegand 26/34 bit, Relay, RS232,RS485, U-disk.
- Can be free standing, mounted to a standard door or pedestrian entrance control turnstile or gate.



HOW TO CONTACT US



North Branch

BFT Automation UK Ltd.

Units C2-C3,

The Embankment Business Park.

Vale Road,

Heaton Mersey,

Stockport.

SK4 3G6L.

South Branch

BFT Automation (South) Ltd.

Enterprise House,

Murdock Road,

Dorcan, Swindon.

SN3 5HY

Telephone:

01614 560 456

Web:

www.bftautomationuk.com

Telephone:

01488 674 750

Web:

www.bftautomationuk.com

Telephone:

+353 1 456 4711

Ireland Branch

Old Ness Road,

Dublin 12.

BFT Automation Ltd.

Unit D3, City Link Business Park.

Web:

www.bftautomationuk.com